

CST454CEF(G) Gwyneth[™] Two-Piece Toilet, 1.28 GPF




CST454CEFG - Gwyneth Two-Piece Toilet



Double Cyclone[™] flushing system with maximum cleaning action for a cleaner toilet bowl.





Choose a SoftClose toilet seat, or upgrade to a Washlet.



Fast Flush: New, wide 3" flush valve is 125% larger than conventional 2" flush valves.

- Sleek high profile twopiece design
- Double Cyclone[®] Technology
- Powerful, quiet flush every time
- Wide, 2-1/8" computer designed trapway
- Large water surface
- Saves 20% water over 1.6gpf toilets.

High profile two-piece toilet. High efficiency (1.28Gpf/ 4.8Lpf) Double Cyclone flushing action.

Tank cover, fittings, polished chrome trip lever included.

CST454CEF Elongated toilet.

CST454CEFG Elongated toilet. SanaGloss[®] glazing.

□ **C454CEF** Elongated front bowl only, 12" rough-in.

C454CEFG

Elongated front bowl only, 12" rough-in. SanaGloss glazing.

🗆 ST454E

Gwyneth tank and cover only. Complete with tank trim and coupling components.

🗆 SS114

SoftClose[®] Seat and lid gently close with a touch of a hand. Elongated, closed front seat with lid.

Colors:

Sanagloss: #01 Cotton, #03 Bone, #11 Colonial White, #12 Sedona Beige Non-Sanagloss: #04 Gray, #51 Ebony

Trip Lever:

Standard #CP Polished Chrome Optional See price book for additional finishes



ADA Height Compliant

Augusta Decorative Collection

CST454CEF(G) Gwyneth[™] Two-Piece Toilet, 1.28 GPF

PERFORMANCE

The TOTO[®] Double Cyclone[®] system offers outstanding commercial grade performance. The TOTO[®] high-efficiency two-piece toilet received high ratings during ANSI/ASME testing at independent laboratories. Designed with a powerful siphon jet flushing action, the bowl offers a large water surface and a 100% glazed trapway.

SPECIFICATIONS

Water Use:	4.8 Lpf/1.28 Gpf
Flush System:	Gravity Feed
	(Double Cyclone® Technology)
Min. Water Pressure:	
	8 psi (Static)
Water Surface:	7-1/8" x 9-1/4"
Trap Dia.:	2-1/8"
Rough-in:	12"
Trap Seal:	2-3/8"
Warranty:	Five Year Limited Warranty
Material:	Vitreous China

Shipping Weight: C454CEF(G) 57.3 lbs. ST454E

31.5 lbs. Shipping Dimensions:

> C454CEF(G) 29" L X 14-3/4" W¹ X 11-1/2" W² X 16-1/4" H ST454E 18" L X 9" W X 16" H

Meets all ASME A112.192.2, CSA B45 Requirements, and LASPS for rebate program.



Meets the American Disabilities Act Guidelines for toilet height and ANSI A117.1 requirements where installed so top of seat is 17"-19" from the finished floor. For installation condition with approach from left-hand side.

Meets and exceeds ASME A112.19.2 standards for drainline carry distance with a 2% grade and 4" I.D. pipe. WaterSense compliant.

These dimensions and specifications are subject to change without notice.



TOTO U.S.A., INC. • 1155 Southern Road, Morrow, GA 30260 Tel. (888) 295-8134 • Fax. (770) 282-8701 • www.totousa.com Printed in U.S.A. © TOTO LTD. 05/08 #A10510

